


AMERICAN STEEL MORTISE TEMPLATE FOR:  
Model Cardlock 1000, 1100 and 1500

Note: Use template for right and left hand doors.

VERSION 6.0 12/3/2008

ASA DOOR STRIKE PREP. (LEFT OR RIGHT)  
RIGHTHAND STRIKE SHOWN BELOW



BeLine  
818.357.5980  
info@belinelocks.com

Place this line on centerline of door thickness to make mortise cutout

For RH & RHR doors with 0° bevel angle.

High Bevel Edge & Low Bevel Edge Indications are for 3° Bevel Angle for 1 3/4" (44mm) Doors.

CENTERLINE OF MORTISE


CENTERLINE OF THE CYLINDER INSERT LOCATION

Cutout for mortise 4+1/4" (110mm) deep  
Cutout for mortise cover plate 1/4" (6mm) deep

3/8" (10mm)

High bevel edge

Low bevel edge



NOTE: CUT BOTH SIDES OF DOOR FOR 1000 SERIES AND 1100 SERIES ONLY.

4 holes 3/8" (9mm) diameter

Low bevel edge High bevel edge

For LH & LHR doors with 0° bevel angle.

CAUTION  
Apply template and drill but compensate for any door bevel and thickness different from the standard shown

Center line of door  
High bevel edge  
Low bevel edge  
RH door shown